

# EVA MS-DIN PLUS










CT DIN Water jacket

## FEATURES AND BENEFITS

- Temperature range  $-20^{\circ}\text{C}$  to  $+150^{\circ}\text{C}$  (according to models).
- Fast temperature regulation by Peltier element.
- Compatible from FIRST PLUS.
- Compatible with coaxial cylinders.

## ACTIVITY DOMAINS

-  Food Industry
-  Cosmetics pharmaceuticals
-  Paint / ink / coatings
-  Chemical / petroleum products
-  Car industry
-  Teaching
-  Chocolate

### TEMPERATURE CONTROL DEVICES AVAILABLE

Compatible only with bayonet coupling device

Designation	Part Number	Temperature range	Type	Prog <sup>c)</sup>	Compatible device	Compatible Measuring system	Size (p×l×h) in mm	Weight
EVA MS DIN PLUS	N950000	$+5^{\circ}\text{C}$ to $+65^{\circ}\text{C}$	Peltier	No	FIRST, RM100 <sup>b)</sup> , RM200, DSR 500	MS DIN, MS SV <sup>d)</sup> , MS ULV, MS-CHOCOLATE	610x340x650	15Kg
EVA MS DIN PLUS	N950003	$-20^{\circ}\text{C}$ to $+100^{\circ}\text{C}$	Peltier <sup>a)</sup>	No				
EVA MS DIN PLUS	N950005	$+5^{\circ}\text{C}$ to $+65^{\circ}\text{C}$	Peltier	Yes				
EVA MS DIN PLUS	N950007	$+5^{\circ}\text{C}$ to $80^{\circ}\text{C}$	Peltier	No				
EVA MS DIN PLUS	N950008	$+0^{\circ}\text{C}$ to $+150^{\circ}\text{C}$	Peltier	No				
EVA MS DIN PLUS	N950009	$+0^{\circ}\text{C}$ to $+150^{\circ}\text{C}$	Peltier	Yes				
EVA 100 PLUS	N950100	Room to $+100^{\circ}\text{C}$	Electrical	No				
CT DIN	111914	$-20^{\circ}\text{C}$ to $+100^{\circ}\text{C}$	Fluid <sup>a)</sup>	No		120x200	4kg	
EVA MS DIN/MS-R PLUS	N950002	$+5^{\circ}\text{C}$ to $+65^{\circ}\text{C}$	Peltier	No	RM100 <sup>b)</sup> , RM200, DSR 500	MS DIN, MS-R	610x340x650	15Kg
EVA MS DIN/MS-R PLUS	N950020	$-20^{\circ}\text{C}$ to $+100^{\circ}\text{C}$	Peltier <sup>a)</sup>	Yes				
EVA MS DIN/MS-R PLUS	N950030	$+0^{\circ}\text{C}$ to $+150^{\circ}\text{C}$	Peltier	No				
EVA MS DIN/MS-R PLUS	N950040	$+0^{\circ}\text{C}$ to $+150^{\circ}\text{C}$	Peltier	Yes				

a) Need a chiller. Not included b) Usable with RM100 Portable and RM100 i

c) Allow temperature setting by RheoTex software or measuring head d) Need to be used with centring tool (PN 114436)